

# BAR GRATING



We manufacture in accordance with NAAMM Standards

ISO 9001:2015 CERTIFIED



## STAIR TREADS - 1" x 3/16" Swage-Locked, Rectangular Bar, Smooth Surface

Product Line .....	Stair Treads
Construction Type .....	Swage-Locked
Bearing Bar Shape .....	Rectangular Bar
Series Type & Name .....	Bar - GAL-100 (Swage-Locked)
Product Spacing .....	19-S-4
Primary Material .....	Aluminum (AL)
Alloy, Grade or Type .....	Alloy 6063-T6 (6063T6)
Material Finish .....	Mill Finish
Bearing Bar Size & Shape .....	1" x 3/16" Rectangular Bar
Bearing Bar Height .....	1"
Bearing Bar Thickness .....	3/16"
Bearing Bar Spacing .....	1-3/16" on Center
Clear Space Between Bearing Bars .....	1"
Product Surface .....	Smooth
Bearing Bar Direction (Span) .....	Parallel to Length of Tread
Cross Bar Type .....	Square Rod
Cross Bar Spacing .....	4" on Center
Nosing Type .....	Corrugated 90° Angle Nosing
Nosing Dimensions (Width) .....	Equal Legs (1-1/4" Leg x 1-1/4" Leg)
Carrier Plates Attached .....	Yes
Carrier Plate Size .....	CP-BG-1230 Bar Grating Stair Tread Carrier Plates - Pair (3" Height x 12-1/8" Width)
Percent Open Area .....	77%
Weight .....	8.09 Lbs./Tread
Product Form .....	Tread
Sizes (Width x Length) .....	12-1/8" x 28"; 12-1/8" x 36"

Direct Metals® Company, LLC makes no representation or warranty (express or implied) regarding these drawings as they are conceptual in nature. It is the customer's responsibility to have all information and products verified to determine the suitability for the application. The customer assumes all risk and liability for any losses, claims or damage resulting from such use. Certain numbers may be rounded up or down for example purposes.